



Adore PB



.....
Data Sheet
.....


www.rexton.com

REXTON 

Adore PB · Technical Data

Type	Earhook		ThinTube	
				
	2 ccm coupler	Ear simulator	2 ccm coupler	Ear simulator
Output sound pressure level				
at 1.6 kHz	–	138 dB SPL	–	128 dB SPL
Peak	135 dB SPL	141 dB SPL	130 dB SPL	133 dB SPL
HFA-OSPL 90	129 dB SPL	–	118 dB SPL	–
Gain				
Full on gain (FOG) at 1.6 kHz	–	76 dB	–	61 dB
Full on gain (peak)	77 dB	81 dB	65 dB	68 dB
HFA-FOG	70 dB	–	55 dB	–
Reference test gain	52 dB	62 dB	41 dB	52 dB
Frequency, noise and directivity				
Frequency range	100 - 6000 Hz	120 - 5900 Hz	100 - 5800 Hz	100 - 5900 Hz
Equivalent input noise	18 dB SPL	17 dB SPL	21 dB SPL	19 dB SPL
Total harmonic distortion at 500 / 800 / 1600 / 3200 Hz	4 / 3 / 1 / 1 %	5 / 4 / 1 / – %	2 / 2 / 1 / 1 %	2 / 2 / 2 / – %
AI-DI	4.0 dB		4.0 dB	
Inductive coil sensitivity				
MASL (1 mA/m) at 1.6 kHz	–	105 dB SPL	–	93 dB SPL
HFA MASL (1 mA/m)	99 dB SPL	–	85 dB SPL	–
HFA SPLITS (left/right)	109 / 109 dB SPL	–	99 / 99 dB SPL	–
RSETS (left/right)	-3 / -3 dB	–	-2 / -2 dB	–
HFA SPLIV	111 dB SPL	–	101 dB SPL	–
Battery				
Battery voltage	1.3 V		1.3 V	
Battery current drain	2.0 mA	2.0 mA	1.7 mA	1.7 mA
Battery life (cell zinc air)	~120 h		~130 h	
Battery life (rechargeable)	–		–	
IRIL IEC 60118-13:2016 Ed. 4.0				
700-960 MHz (rating)	user		user	
1400-2000 MHz (rating)	user		user	
2000-2700 MHz (rating)	user		user	
ANSI C63.19-2011				
800-950 MHz (rating)	M4 / T4		M4 / T4	
1600-2500 MHz (rating)	M4 / T4		M4 / T4	


Adore PB · Fitting Range



Earhook · Basic Data


2 ccm coupler

Ear simulator




Output sound pressure level
($L_i = 90$ dB)

Full on gain
($L_i = 50$ dB)




Output sound pressure level
($L_i = 90$ dB)

Full on gain
($L_i = 50$ dB)




Frequency response
($L_i = 60$ dB)




Basic acoustic response
($L_i = 60$ dB)

Inductive response




Inductive response
($H = 10$ mA/m)



SPLITS curve left
($H = 31.6$ mA/m)


SPLITS curve right
($H = 31.6$ mA/m)



SPLIV curve
($H = 31.6$ mA/m)


ThinTube · Basic Data

2 ccm coupler




Output sound pressure level
($L_1 = 90$ dB)

Full on gain
($L_1 = 50$ dB)




Frequency response
($L_1 = 60$ dB)

Ear simulator




Output sound pressure level
($L_1 = 90$ dB)

Full on gain
($L_1 = 50$ dB)




Basic acoustic response
($L_1 = 60$ dB)

Inductive response




Inductive response
($H = 10$ mA/m)



SPLITS curve left
($H = 31.6$ mA/m)

SPLITS curve right
($H = 31.6$ mA/m)



SPLIV curve
($H = 31.6$ mA/m)

Adore PB | Features and Accessories

MyCore Platform

Signal processing (channels) / Gain/MPO (handles)

48 / 20

Hearing programs

6

Direct Audio Streaming ¹⁾ / Made for iPhone

●

My Voice ²⁾

●

Wireless Sync ²⁾

●

Volume and control coupling ²⁾

●

MyCore Speech

HD Bandwidth (up to 10 kHz)

●

iFocus 360 ²⁾

automatic

Focus 360

●

HD Directionality

●

Stereo iLock ²⁾

●

Directional iLock ²⁾

Premium

Voice Ranger

●

XPhone ²⁾

●

Multichannel Adaptive Directional Microphone

●

Automatic Directional Microphone

●

Fixed Directional Microphone

●

Bandwidth Compression

●

Intelligent Feedback Preventer

●

MyCore Sound Quality and Comfort

Dynamic Extender

●

Auto Volume ³⁾

●

Microphone-pattern adjustment ^{2), 4)}

Premium

Reverb Reducer

●

Music Enhancer

Premium

iOmni

●

Sound Smoothing (settings)

3

Intelligent Wind Noise Cancellation ²⁾

Premium

Wind Noise Cancellation

●

Noise Management

●

MyCore Automatic Optimization

Smart Automatic Equalizer

Premium

Smart Automatic Acclimatization

Premium

Automatic Classifier

●

Data Logging

●

¹⁾ Apple iPhones 5 and later

²⁾ Bilateral fitting required

³⁾ Streaming only

⁴⁾ requires Connexx Smart Direct App

⁵⁾ Availability is country-dependent

● available – not available

Performance levels: Premium

Adore PB | Features and Accessories

Style specific features	
SecureTec protection	IP68
Charging contacts	–
Battery Size	13
Battery door on/off function	●
Nanocoated housing	●
Wireless programming	●
Instrument configurations	
Flat cover	–
Rotary volume control	–
Push button	–
Rocker switch	●
Color conversion kit	○
Battery door - integrated telecoil	○
Battery door - child lock	–
Small earhook	○
Programming accessories	
ConnexxAir / ConnexxLink	– / –
Noahlink Wireless	●
HI-PRO 2: adapter/cable	size 13
Accessories	
Connexx Smart Key	○
Connexx Smart Transmitter 2,4	○
Connexx Smart Mic	○
Apps	
Connexx Smart Direct App	○
Connexx Smart Remote App	○

● available ○ optional – not available

Adore PB

Abbreviations and Standards

Abbreviations

The following abbreviations are used in this datasheet:

OSPL	Output Sound Pressure Level
HFA	High Frequency Average
FOG	Full-On Gain
MASL	Magneto Acoustical Sensitivity Level
SPLITS	Coupler SPL for an Inductive Telephone Simulator
RSETS	Relative Equivalent Telephone Sensitivity
SPLIV	SPL In a Vertical magnetic field
AI-DI	Articulation Index - Directivity Index
IRIL	Input Related Interference Level
RTF	Reference Test Frequency

Standards

- ▶ All measurements with the 2 ccm coupler were performed according to ANSI S3.22-2014 and IEC 60118-0:2015 if applicable.
- ▶ All measurements with an ear simulator were performed according to IEC 118-0/A1:1994 and to DIN 45605 (frequency range) if applicable.
- ▶ Curves and figures representing FOG are measured with 20 dB reduction and 70 dB SPL input level.
- ▶ Figures representing Equivalent Input Noise incorporate a moderate expansion.
- ▶ Inductive coil sensitivity values, inductive response curves and T ratings apply for instruments with telecoil battery door only.
- ▶ The current consumption is measured in reference test setting (RTS) according to the applicable standards. Due to the settling behaviour of hearing instruments supporting RF (radio frequency), the battery current is measured 3 minutes after turning on (note: no pairing).
- ▶ The battery life is based on first fit settings using 60% of the fitting range and an ISTS (International Speech Test Signal) input signal at 65 dB SPL (note: pairing established). The actual battery life is determined by battery quality, hearing loss, sound environment, usage and activated feature set.
- ▶ The following acoustic connections / ear pieces were used:
 - Earhook
 - ThinTube
- ▶ HD Bandwidth up to 10 kHz for 80 8C devices only.



“Made for iPhone” means that an electronic accessory has been designed to connect specifically to iPhone and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPhone may affect wireless performance.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice.

The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

Legal Manufacturer
Sivantos GmbH
Henri-Dunant-Strasse 100, 91058 Erlangen
Germany

Subject to change without prior notice

Order No. 03612-99T1-7600
© 06.2018, Sivantos GmbH
All rights reserved

WARNING

Choking hazard posed by small parts.
▶ This instrument is not intended for the fitting of infants, children under 3 years or persons of mental incapacity.

WARNING

Instrument has an output sound pressure level of 132 dB SPL or more. Risk of impairing the residual hearing of the user.
▶ Take special care when fitting this instrument.

REXTON 