

Adore™ PB BTE Hearing Aid

Standard ANSI S3.22-2014		2 ccm coupler
Output	Peak OSL 90 HF - average OSPL 90	135 dB 129 dB
Full-on gain	Peak HF-average	77 dB 70 dB
Frequency Range	Low frequency limit High frequency limit	100 Hz 6000 Hz
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	4% 3% 1% 1%
Equivalent Input Noise		18 dB
Battery Current Drain		2.0 mA
Battery life (typical)	13 zinc air battery	~120 hrs.

All data specified were determined under test conditions which comply with the Specifications of Hearing Aid Characteristics ANSI S3.22-2014.

Hearing aid test settings according to the test mode, selectable from the Connexx® fitting menu, configures the instrument for full-on gain, no compression and all adaptive signal analysis and processing turned off.


Battery life stated is measured at 65 dB input and reference test gain.

Actual battery life depends on the output level.


All tests performed with earhook.

Hearing instruments made in Singapore.
Rev. 10/18 PN 10240641 1.0 RX18808


Output Sound Pressure Level



Frequency Response



Inductive Response



Adore™ PB BTE Hearing Aid

Standard ANSI S3.22-2014		2 ccm coupler
Output	Peak OSL 90 HF - average OSPL 90	135 dB 129 dB
Full-on gain	Peak HF-average	77 dB 70 dB
Frequency Range	Low frequency limit High frequency limit	100 Hz 6000 Hz
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	4% 3% 1% 1%
Equivalent Input Noise		18 dB
Battery Current Drain		2.0 mA
Battery life (typical)	13 zinc air battery	~120 hrs.

All data specified were determined under test conditions which comply with the Specifications of Hearing Aid Characteristics ANSI S3.22-2014.

Hearing aid test settings according to the test mode, selectable from the Connexx® fitting menu, configures the instrument for full-on gain, no compression and all adaptive signal analysis and processing turned off.


Battery life stated is measured at 65 dB input and reference test gain.

Actual battery life depends on the output level.


All tests performed with earhook.

Hearing instruments made in Singapore.
Rev. 10/18 PN 10240641 1.0 RX18808


Output Sound Pressure Level



Frequency Response



Inductive Response



Adore™ PB BTE Hearing Aid

Standard ANSI S3.22-2014		2 ccm coupler
Output	Peak OSL 90 HF - average OSPL 90	135 dB 129 dB
Full-on gain	Peak HF-average	77 dB 70 dB
Frequency Range	Low frequency limit High frequency limit	100 Hz 6000 Hz
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	4% 3% 1% 1%
Equivalent Input Noise		18 dB
Battery Current Drain		2.0 mA
Battery life (typical)	13 zinc air battery	~120 hrs.

All data specified were determined under test conditions which comply with the Specifications of Hearing Aid Characteristics ANSI S3.22-2014.

Hearing aid test settings according to the test mode, selectable from the Connexx® fitting menu, configures the instrument for full-on gain, no compression and all adaptive signal analysis and processing turned off.


Battery life stated is measured at 65 dB input and reference test gain.

Actual battery life depends on the output level.


All tests performed with earhook.

Hearing instruments made in Singapore.
Rev. 10/18 PN 10240641 1.0 RX18808


Output Sound Pressure Level



Frequency Response



Inductive Response



Adore™ PB BTE Hearing Aid

Standard ANSI S3.22-2014		2 ccm coupler
Output	Peak OSL 90 HF - average OSPL 90	135 dB 129 dB
Full-on gain	Peak HF-average	77 dB 70 dB
Frequency Range	Low frequency limit High frequency limit	100 Hz 6000 Hz
Total harmonic distortion	500 Hz 800 Hz 1600 Hz 3200 Hz	4% 3% 1% 1%
Equivalent Input Noise		18 dB
Battery Current Drain		2.0 mA
Battery life (typical)	13 zinc air battery	~120 hrs.

All data specified were determined under test conditions which comply with the Specifications of Hearing Aid Characteristics ANSI S3.22-2014.

Hearing aid test settings according to the test mode, selectable from the Connexx® fitting menu, configures the instrument for full-on gain, no compression and all adaptive signal analysis and processing turned off.


Battery life stated is measured at 65 dB input and reference test gain.

Actual battery life depends on the output level.


All tests performed with earhook.

Hearing instruments made in Singapore.
Rev. 10/18 PN 10240641 1.0 RX18808

Output Sound Pressure Level



Frequency Response



Inductive Response

